

# KS-8890

## DATENBLATT DATA SHEET



**KSE-LIGHTS**  
be tough • be safe • be different

<b>LICHT LIGHT</b>	Name//Name Art.-Nr. // Art. No. max. Lumen // max. lumens max. Distanz // max. distance Anz. Schaltstufen // no. of modes Optiken // optics Optik #1 // optic #1 Leuchtmittel // light source	KS-8890 KS-8890 323 lm 290 m 2 Reflektor // reflector 6000 Kelvin Cree XP-G LED
<b>SCHALTSTUFEN LIGHT MODES</b>	<b>Powermodus // power mode</b> Lumen // lumens Distanz // distance Leuchtzeit // luminous time	KS-8890 323 lm 290 m 6h
	<b>Arbeitsmodus // working mode</b> Lumen // lumens Distanz // distance Leuchtzeit // luminous time	KS-8890 140 lm 190 m 13 h
<b>SICHERHEIT SAFETY</b>	Zertifikate // certificates ATEX IECEX	KS-8890 Ja // yes Ja // yes
	Geräteklasse // equipment class Geräteklasse // equipment class zulässige Temp. // allowed temp.	II 1G Ex ia IIC T4 Gb I M1 Ex ia I Ma -20 °C <Ta< +40 °C
<b>GENERELLES GENERAL</b>	Generelles // general Schutzklasse // protection class Gehäusematerial // housing material Gehäusefarbe // color of housing Gewicht // weight Garantie // warranty	KS-8890 IP54 Kunststoff // plastic Gelb & Schwarz // black & yellow 250 g (ohne Batterien // without batteries) 2 Jahre // 2 years
	Batterien // batteries	4x AA
	Zolltarifnummern // customs tariff numbers Ursprungsland // country of origin Produktmaße // product dimensions Maße Verpackung // packing dimensions	8513 1000 China // China 65mm x 60mm x 190mm 75mm x 68mm x 195mm
	Lieferumfang // scope of delivery Lieferumfang // scope of delivery Lieferumfang // scope of delivery Lieferumfang // scope of delivery	KS-8890 Standardclip // standard clip Anleitung // manual Batterien nicht enthalten // batteries not included
15.03.2022	Erstellt durch KSE-Lights Erstelldatum Irrtümer vorbehalten	Rückfragen // questions? -> +49 (0) 23 33 - 982 47 30 <a href="http://www.kse-lights.com">www.kse-lights.com</a> <a href="http://www.shop.kse-lights.com">www.shop.kse-lights.com</a> <a href="#">KSE-Instagram</a> <a href="#">KSE-Facebook</a>