



BH-90A
Portable Single
Gas Detector

Technical Parameters

Alarm methods: sound, light, vibration

Working Temperature: -20°C-50°C

Power: 3.7V rechargeable lithium battery


Sensor life: 2 years

Charging time: 4~6hours

Display: 1.77 inch LCD display

Operating time: working continuously for at least 8 hours

Explosion-proof: Exib IIB T3 Gb



Size: 109x60x30mm

www.bosean.com Q

BH-90A Portable Single Gas Detector

BH-90A is an economical single gas detector, adopting advanced sensor and micro control technical, quick response, high accuracy, great steadily and repeatability, the detector's performance is the leader grade in the industry, easy to operate.

The detector has built in large and rechargeable lithium battery, long standby; adopt LCD screen that can indicate every technical data and gas concentration value perfectly. The shell is designed by anti slip material, small and portable. Suitable for explosion proof, toxic gas leak rescue, underground pipe, mine, metallurgy ,electric industry, chemical, tunnel and other places. prevent the accident efficiently, keep the worker safe and prevent the facilities from being destroyed.





methods











(2) HOTLINE: +86 15639790605

□ Sensors supported


Can detect more than 30 kinds of gases, can customize flexibly according to users' need (detect 4 different gases in one unit). normally detect Ex, O2,H2S,CO gases.

¦ Range

EX: $0\sim100\%$ LEL O_2 : $0\sim30\%$ VOL H_2 S: $0\sim100$ PPM CO: $0\sim1000$ PPM

Resolution

EX: 1%LEL
O₂: 0.1%VOL
H₂S: 1PPM
CO: 1PPM



- 1、Gas display
- 2. Gas concentration content display
- 3, Battery power display
- 4. Unit power display
- 5. Time display
- 6. Temperature display







→ +86 371-86533226
 → sales@bosean.com
 ◆ 10th Floor, Building 10, Enterprise Park, No. 228,
 West Fourth Ring, High-tech Zone, Zhengzhou City