



**RAE Systems by Honeywell
Fixed-Head Wireless Infrastructure**

RAEPoint

Fixed-Head Wireless Infrastructure



Key Features

- 5 internal SPDT relays
- Wireless transmission distance of 300 m (1000 ft) point-to-point. Range can be extended by using wireless routers
- Continuously powered by standard 12-28VDC input
- Class 1, Division 1 (ATEX Zone 1 hazardous area certification)
- Available as stand-alone unit, or as a turn-key wireless alarm bar solution, mounted and pre-wired with two 5J xenon lights and a 110dB horn

Applications

- Oil and gas exploration
- Worker exposure monitoring
- Fenceline monitoring

RAEPoint is a multi-function wireless infrastructure component for RAE Systems by Honeywell wireless gas detection systems.

This key building block can operate as an access point in hazardous areas to communicate with wireless gas detectors to enable integration with FMC-2000 or PC-based ProRAE Guardian host controllers. When directed by the controller, the RAEPoint can use any of its five internal relays to trigger audible and visible alarms to provide additional alert notification in hazardous locations. Additionally, the RAEPoint operates as a range extender to increase the wireless transmission distance of wireless gas detectors.



RAEPoint

Fixed-Head Wireless Infrastructure Specifications



RAEPoint Specifications

Basic parameters

| | |
|----------------------|---|
| Input/Output | Power Input: 2.4W Vinut: 12-28VDC 5 SPDT relays Resistor load max: 6A@24VDC or 6A@250VAC Inductive load max: 2A@24VDC or 3A@250VAC |
| Wireless | IEEE 802.15.4 ISM band |
| Transmission Range | 300m (1000 ft) typical |
| IP Rating | IP-65 |
| Mechanical Interface | 3/4" NPT female |
| Installation | 50.8 mm (2") pipe-holding or wall mounting |

Environmental parameters

| | |
|-------------|--|
| Temperature | -20° C to +55° C (-4° F to 131° F) |
| Humidity | 0 to 95% relative humidity, non-condensing |
| Pressure | 90 to 110kPa |

Display

| | |
|---------|--|
| Display | 4 LEDs (Network, Alarm, Communication, Mode) |
|---------|--|

Physical parameters

| | |
|------------------|--|
| Dimensions | 257 x 201 x 107 mm (10.1" x 7.9" x 4.2") |
| Housing Material | Aluminum |
| Weight | 3.5 kg (7.7 lbs) |

Certification

| | |
|----------------------|---|
| Safety Certification | IECEX: Ex d ia IIC T6, Gb ATEX: Ex II 2G, Ex d ia IIC T6 Gb cCSAus: Class I, Division 1 Group A,B,C,D T6 |
| | Wireless certification FCC Part 15 R&TTE directive (1999/5/EC) (Contact RAE Systems for other countries.) |

Ordering Options

The RAEPoint can be ordered as a stand-alone wireless unit, or as an integrated Wireless Alarm Bar complete with two strobes and one horn. Each RAEPoint can be configured as a Router, Remote, or Host on a wireless mesh network. Configurations include:

RAEPoint Router

A stand-alone, DC-powered, explosion-proof unit that acts as a permanent wireless router for mesh network systems. Includes an aluminum enclosure with LED status indicators and an integrated wireless mesh radio.

RAEPoint Remote & RAEPoint Host

Stand-alone relay units include an aluminum enclosure with LED status indicators, an integrated wireless mesh radio, and five integrated relays.

