

CROWCON
Detecting Gas Saving Lives

Detective+

Temporary Area Monitor

Rugged tripod design
Loud and clear alarms
Network ready



Detective+

Transportable Multi-gas Area Monitor

The Detective+ is a rugged, water and impact resistant multi-gas monitor for temporary areas. Ideal for use in turnaround/shutdown procedures, hot work maintenance, confined space entry work and many other utility, construction and oil and gas industry applications. Detective+ gives a loud and clear alarm providing effective warning of gas hazards. The rugged, water and impact resistant design make Detective+ the ideal choice for your transportable gas detection needs.



Versatile and user friendly

Infrared sensors available	Allows sampling of highly flammable gas levels and carbon dioxide Unaffected by poisoning and has a very fast response time
Built in pump option	Provides sampling versatility
Built-in display	Provides clear information, allows identification of gas hazard

Rugged, tripod design

Raised sensor apertures	Prevents water ingress
Triple leg design	Increases unit physical visibility and is the perfect height to allow 360 gas inlet
Folding leg option	Allows stacking for easier storage and transportation
IP65 specifications	Provides excellent sensor protection for use in challenging environments

Loud and clear alarms

Network ready	25 units can be networked together forming effective perimeter defence. When one alarms, all units on the network alarm. Detective+ with cables 12 units
Intelligent & flexible	Units on the network can be placed up to 100m from each other. When in alarm the unit which triggered the alarm flashes faster than the others
Audible and visible confidence blip	Provides guarantee to the user that the unit is functioning properly and that they are protected
High visibility	Vivid red LED clusters combine with an extra loud siren to give very clear alarm notifications
Multiple beacons	Ensures 360° visibility

Gases and ranges

Gas	Range	Typical alarms
Flammable gas	0-100% LEL	20% LEL
Oxygen (O ₂)	0-25%	19% & 23%
Hydrogen sulphide (H ₂ S)	0-50ppm	10ppm
Carbon monoxide (CO)	0-500ppm	30ppm
Sulphur dioxide (SO ₂)	0-10ppm	2ppm
Chlorine (Cl ₂) ⁺	0-5ppm	0.5ppm
Nitrogen dioxide (NO ₂)	0-10ppm	2ppm
Phosphine (PH ₃)	0-5ppm	0.5ppm
Ammonia (NH ₃)	0-50ppm	25ppm
Ammonia (NH ₃)	0-1000ppm	n/a
Hydrogen (non-flammable levels)	0-2000ppm	n/a
Hydrogen cyanide (HCN)	0-25ppm	10ppm
Hydrogen chloride (HCl) ^{*/+}	0-10ppm	5ppm
Chlorine dioxide (ClO ₂) ⁺	0-1ppm	0.1ppm
Hydrogen fluoride (HF) ⁺	0-10ppm	1ppm
Ethylene oxide (C ₂ H ₄ O) [*]	0-10ppm	5ppm
Volatile organic ^{*/+}	0-100ppm	n/a

Required ranges and alarms may vary by country and application and these can be configured as required.

* One biased sensor per Detective+

⁺ Reactive gas, care required during sampling, contact Crowcon for details.

Infrared sensors

Infrared (IR) sensors for flammable gas can be supplied as a single range, 0-100% LEL, utilising a single display channel, or as a dual range, 0-100% LEL/0-100% volume, which then occupies two display channels.

Carbon dioxide sensors are supplied as 0-5% volume. Only one IR sensor can be fitted, and IR sensors can only be used in combination with oxygen and toxic sensors.

Gas	Range	Typical alarms
Flammable gas	0-100% LEL	20% LEL
Flammable gas	0-100% v/v	None
Available for methane, propane, butane or ethylene		
Carbon dioxide (CO ₂)	0 to 5% v/v	0.5 and 1.5% v/v

Specification

Size	640 x 455 x 455mm (25.2 x 17.9 x 17.9ins)
Weight	7.5kg (19lbs)
Visible Alarms	Three large, top mounted red LED clusters and a single red LED on front panel. Alarm mode: LED clusters flash in quick succession. LED clusters of linked Detectives repeating the alarm, flash slower than LED lights on those Detectives sensing the hazard. Normal working: Slow flashing green LED Battery low: Rapid flashing green LED
Audible Alarms	Wailing, omni-direction siren, 104 dBA at 1m
Display	High contrast LCD with backlight. Values and units for up to 4 gases displayed simultaneously at current, TWA or peak levels, low battery, real time and elapsed time calibration and configuration data also displayed
Data logging	125hrs at 10-second intervals (45,000 logs)
Event logging	Alarm, over range, calibration, bump, on/off, TWA, 1000 events
Battery	Standard 6V, 7.2Ah, sealed lead acid battery pack Optional 6V, 12Ah high capacity pack Up to 36 hours with 7.2Ah battery Up to 60 hours with optional 12A battery
Typical response times	Methane 20s, oxygen 10s, typical toxic gas 20s, IR 20s
Expected sensor life	Flammable 5 years, toxic 3 years (typical), oxygen 2 years minimum, IR >5 years
Operating temperature range	-20°C to + 50°C (-4°F to 122°F)*
Humidity	15–95% RH non-condensing**
Approvals	Europe: ATEX II 2G Ex ib d IIC T4 (Tamb -20°C to + 50°C) International: IECEx Ex ib d IIC T4 (Tamb -20°C to +50°C)
Standards	EN50014, EN50018, EN50020, EN50104, EN45544, IEC60079-0/-1 IEC60079-11
Ingress protection	IP65
EMC	FCC CFR47 Part 15, Directive 2014/30/EU EN50270
PC interface	Via RS232 lead. Portables PC software can be used to set alarms, clock, data logging interval and password, manages data logging giving graphical display of instrument log file and allows to export to spreadsheet
Calibration	Quick calibration using internal menu command, Portables PC
Accessories	Baffle plate, interconnecting leads, RS232 communications lead
Sampling	Internal electric sampling pump option, manual aspiration
Linked detectives	With cable connection, up to 12 units can be linked to provide perimeter or area monitoring

- * Toxic and oxygen sensors are not rated for continuous operation at high temperatures.
Consult Crowcon if operating temperatures are likely to exceed 40°C (104°F) for extended periods.
** Toxic and oxygen sensors RH specifications vary, consult Crowcon for specific operating humidities.

Disclaimer

Every effort has been made to ensure the accuracy of this document at the time of printing. In Many factors beyond Crowcon Detection Instruments' control and uniquely within user's knowledge accordance with the company's policy of continued product improvement Crowcon Detection and control can affect the use and performance of a Crowcon product in a particular application. Instruments Limited reserves the right to make product changes without notice. The products are As the products may be used by the client in circumstances beyond the knowledge and routinely subject to a programme of testing which may result in some changes in the characteristics

control of Crowcon Detection Instruments Limited, we cannot determine the relevance of quoted. Technical information contained in this document or otherwise provided by Crowcon these to an individual customer's application. It is the clients' sole responsibility to carry out are based upon records, tests, or experience that the company believes to be reliable, but the the necessary tests to evaluate the usefulness of the products and review all applicable accuracy, completeness, and representative nature of such information is not guaranteed. regulations and standards to ensure their safety of operation in a particular application.

 **CROWCON**
Detecting Gas *Saving Lives*

Crowcon reserves the right to change the design or specification of the product without notice.
© 2023 Crowcon Detection Instruments Ltd. Copyright to some photographs held separately.

www.crowcon.com